Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Chemsure 6002

- · Article number: Chemsure 6002 Part A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**Chemsure Adhesives Ltd** 

Long Lane Winsford Cheshire CW7 4DN

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



Xi; Sensitising

R43: May cause sensitisation by skin contact.

R10: Flammable.

Information concerning particular hazards for human and

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulatio n.

(Contd. on page 2)

Printing date 14.08.2014 *Version number 68* Revision: 14.08.2014

Trade name: Chemsure 6002 Part A

(Contd. of page 1)

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger

· Hazard-determining components of

**labelling:** methyl methacrylate 2-hydroxyethyl methacrylate 2,3-epoxypropyl methacrylate hydroquinone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

· **Description**: Adhesive.

· Dangerous compon	ents:	
CAS: 80-62-6 EINECS: 201-297-	methyl methacrylate  Xi R37/38; Xi R43;  F R11	25-50%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT S 3, H335	Е
CAS: 868-77-9 EINECS: 212-782-	2-hydroxyethyl methacrylate  Xi R36/38; Xi R43	10-25%
212 702	\$\igcup\$ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 106-91-2 EINECS: 203-441-	2,3-epoxypropyl methacrylate  Xn R20/21/22; Xi R36/38; Xi R43  ↑ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.	1-5%
	2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 80-15-9 EINECS: 201-254-	, -dimethylbenzyl hydroperoxide  ☐ T R23; ☐ C R3 4, ☐ Xn R21/22-48/20/22; ☐ O R 7; ☐ N R51/53  ☐ Org. Perox. EF, H242; ☐ Acute Tox. 3, H331; ☐ STOT RE 2, H373;	< 2.5%
	Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	
CAS: 123-31-9	hydroquinone	< 0.5%
EINECS: 204-617-8	Xn R22-40-6 8, Xi R4 1, Xi R4 3, NR5 0 Carc. Cat. 3, Muta. Cat. 3	
	<ul> <li>Muta. 2, H341; Carc. 2, H351;</li> <li>♠ Eye Dam. 1, H318;</li> <li>♠ Acute Tox. 4, H302; Skin Sens. 1, H317</li> </ul> Aquatic	
	Acute 1, H40 0; (Con	td. on page 3

GB

Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

Trade name: Chemsure 6002 Part A

(Contd. of page 2)

· Additional information For the wording of the listed risk phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General informatio **n** Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing In case of persistent symptoms consult doctor.
- d No further relevant information · 4.2 Most important symptoms and effects, both acute and delaye available. 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

· 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency

**procedures** Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing

• 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

Printing date 14.08.2014 *Version number 68* Revision: 14.08.2014

Trade name: Chemsure 6002 Part A

(Contd. of page 3)

### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

## · 7.2 Conditions for safe storage, including any incompatibilities · Storage

- Requirements to be met by storerooms and containers: Store in cool location. Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Storage class 3

## SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems : No further data; see item

#### 7. · 8.1 Control parameters

#### · Components with limit values that require monitoring at the workplace:

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

- · Additional information: The lists that were valid during the compilation were used as basi s.
- · 8.2 Exposure controls
- · Personal protective equipment
- · General protective and hygienic measures

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

Not necessary if room is well-ventilated.

Use breathing protection in case of insufficient ventilation.

#### · Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

**Trade name: Chemsure** 

6002 Part A

(Contd. of page 4)

· Eye protection: Tightly sealed safety glasses.

#### SECTION 9: Physical and chemical properties

· 9.1	Information	on	basic	physical	and	chemical
proper	rties · General	Info	rmatio	n		

· Appearance:

Form: Fluid Colour: Green · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined.

· Change in condition

Melting point/Melting range: Not determined **Boiling point/Boiling range:** 101 °C

10 °C · Flash point:

· Inflammability (solid, gaseous) Not applicable.

430 °C · Ignition temperature:

Not determined. · Decomposition temperature:

· Self-inflammability: Product is not selfigniting.

· Danger of explosion: Product is not explosive.

· Critical values for explosion:

Lower 2.1 Vol % Upper: 12.5 Vol %

: 47 hPa · Vapour pressure at 20 °C

· Density at 20 °C 1.01 g/cm<sup>3</sup> · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

dynamic at 20 °C: 1000 mPas kinematic: Not determined.

· Solvent content:

0.0 % **Organic solvents:** Water: 0.0 % VOC (EU 0.00 %

0.2 % **Solids content:** 

· 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing date 14.08.2014 *Version number 68* Revision: 14.08.2014

Trade name: Chemsure 6002 Part A

(Contd. of page 5)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
106-91-2 2	106-91-2 2,3-epoxypropyl methacrylate				
Oral	LD50	597 mg/kg			
Dermal	LD50	469 mg/kg			
<i>80-15-9</i> ,	-dimethy	blbenzyl hydroperoxide			
Oral	LD50	382 mg/kg			
Dermal	LD50	500 mg/kg			
Inhalative	LC50/4 h	220 mg/l			

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · Sensitization : Sensitization possible by skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradabilit y No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effect

s No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

(Contd. on page 7)

Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

Trade name: Chemsure 6002Part A

(Contd. of page 6) 08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

- $\cdot \ Uncleaned \ packagings:$
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport inform	ation
· 14.1 UN-Number · ADR, IMDG, IATA	
<ul> <li>· 14.2 UN proper shipping name</li> <li>· AD</li> <li>· IMDG, IATA</li> </ul>	R 1133 ADHESIVES (vapour pressure at 50 °C not more than 110 kPa) ADHESIVES
· 14.3 Transport hazard	
class(es) · ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine	pollutant:
<ul><li>14.6 Special precautions for user</li><li>Kemler Number:</li><li>EMS Number:</li></ul>	Warning: Flammable liquids. 33 F-E,S-D
· 14.7 Transport in bulk according to A MARPOL73/78 and the IBC Code	nnex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul><li>Transport category</li><li>Tunnel restriction code</li></ul>	2 D/E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation''	: UN1133, ADHESIVES (vapour pressure at 50 °C not mothan 110 kPa), 3, II

Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

Trade name: Chemsure

6002Part A

(Contd. of page 7)

## SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- · Signal word Danger
- · Hazard-determining components of labelling:

methyl methacrylate

2-hydroxyethyl methacrylate

2,3-epoxypropyl methacrylate

hydroquinone

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · National regulations

### · Technical instructions (air):

Class	Share in 6	%
I	2.2	

- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried

#### SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H225 Highly flammable liquid and vapour.

H242 Heating may cause a fire.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

(Contd. on page 9)

Printing date 14.08.2014 Version number 68 Revision: 14.08.2014

Trade name: Chemsure 6002 Part A

(Contd. of page 8)

H373	May cause damage to organs through prolonged or repeated exposure.	

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

R11 Highly flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R22 Harmful if swallowed. R23 Toxic by inhalation.

R34 Causes burns.

Irritating to eyes and skin. R36/38

R37/38 Irritating to respiratory system and skin. R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

May cause sensitisation by skin contact. R43

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

Very toxic to aquatic organisms. R50

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53

Possible risk of irreversible effects. R68

R7 May cause fire.

#### · Department issuing data specification sheet: Environment protection department.

· Contact: Sales office

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Org. Perox. EF: Organic Peroxides, Types E, F

Acute Tox. 4: Acute toxicity, Hazard Category 4

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 2: Germ cell mutagenicity, Hazard Category 2

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

## \*SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Chemsure 6002 Chemsure 6002 Part B
- · Article number: Chemsure Part B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Chemsure Adheisves Ltd The Old Post Office Off Long Lane Winsford Cheshire CW7 4DN

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F; Highly flammable

R11: Highly flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

Trade name: Chemsure 6002Part

(Contd. of page 1)

#### · Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS05, GHS07
- · Signal wor d Danger

## · Hazard-determining components of labelling:

methyl methacrylate methacrylic acid

2-hydroxyethyl methacrylate

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation. H318 Causes serious eye damage. H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor. P310

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · **Description**: Adhesive.

· Dangerous components:				
CAS: 80-62-6	methyl methacrylate	25-50%		
EINECS: 201-297-	<b>X</b> i R37/3 8, <b>X</b> i R4 3, <b>№</b> F R11			
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT S 3, H335	Е		
CAS: 868-77-9	hydroxyethyl methacrylate			
EINECS: 212-782-	Xi R36/38; Xi R43			
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317			
CAS: 79-41-4	methacrylic acid	1-5%		
EINECS: 201-204-	☑ C R35; 🗙 Xn R21/22			
	Skin Corr. 1A, H31	1		

· Additional information For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General informatio **n** Instantly remove any clothing soiled by the product.

(Contd. on page 3)

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

Trade name: Chemsure 6002 Part B

(Contd. of page 2)

#### · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delaye available. 4.3 Indication of any immediate medical attention and special treatment needed

  No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents

Water.

Water with a full water iet.

· 5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency

**procedures** Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

· 6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

 $\cdot$  6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

(Contd. on page 4)

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

Trade name: Chemsure 6002 Part B

(Contd. of page 3)

Protect from heat.

Protect against electrostatic charges.

 $\cdot$  7.2 Conditions for safe storage, including any incompatibilities  $\cdot$  Storage

- Requirements to be met by storerooms and containers: Store in cool location. Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

- · Storage class 3
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item

#### 7. · 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:

#### 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

#### 79-41-4 methacrylic acid

WEL Short-term value: 143 mg/m³, 40 ppm Long-term value: 72 mg/m³, 20 ppm

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- $\cdot \ General \ protective \ and \ hygienic \ measures$

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

 $\cdot \ Breathing \ equipment:$ 

Not necessary if room is well-ventilated.

Use breathing protection in case of insufficient ventilation.

· Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

· Eye protection: Tightly sealed safety glasses.

CD

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

Trade name: Chemsure 6002 Part B

(Contd. of page 4)

## **SECTION** 9: Physical and chemical properties

	9.1	Information	on	basic	physical	and	chemical
р	rope	rties · General	Info	rmatio	n		

· Appearance:

Form: Fluid
Colour: Pink

Odour: Characteristic
Odour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/Melting range: Not determined Boiling point/Boiling range: 101 °C

· Flash point:  $10 \, ^{\circ}\mathrm{C}$ 

· Inflammability (solid, gaseous) Not applicable.

· Ignition temperature: 430 °C

• **Decomposition temperature:** Not determined.

· **Self-inflammability:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive.

· Critical values for explosion:

 Lower
 : 2.1 Vol %

 Upper:
 12.5 Vol %

· Vapour pressure at 20 °C: 47 hPa

Density at 20 °C
 Relative density
 Vapour density
 Evaporation rate
 1.01 g/cm³
 Not determined.
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix

- · Partition coefficient (n-octanol/water): Not determined.
- · Viscosity:

**dynamic at 20 °C:** 3000 mPas **kinematic:** Not determined.

· Solvent content:

 Organic solvents
 : 0.0 %

 Water :
 0.0 %

 VOC (EU
 ) 0.00 %

Solids content: 10.0 %

• **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided : No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 14.08.2014 Version number 43 Revision: 14.08.2014

Trade name: Chemsure

6002 Part B

(Contd. of page 5)

· 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

#### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritant effect.
- Sensitization : Sensitization possible by skin contact.
- · Additional toxicological information: Irritant

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradabilit y No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

<ul> <li>Europear</li> </ul>	ı waste	cata	logue
------------------------------	---------	------	-------

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 04 00 wastes from MFSU of adhesives and sealants (including waterproofing products)

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to offi08 04 09\* waste adhesives and

#### SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA
- · 14.2 UN proper shipping name
- · ADR

1133 ADHESIVES (vapour pressure at 50  $^{\circ}\text{C}$  not more than 110 kPa)

(Contd. on page 7)

Printing date 14.08.2014 *Version number 43* Revision: 14.08.2014

Trade name: Chemsure 6002 Part B

	(Contd. of page 6)
· IMDG, IATA	ADHESIVES
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
3	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine	pollutant:
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
· EMS Number:	F-E,S-D
· 14.7 Transport in bulk according to Ai MARPOL73/78 and the IBC Code	nnex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml
<ul><li> Transport category</li><li> Tunnel restriction code</li></ul>	Maximum net quantity per outer packaging: 500 ml 2 D/E
<ul><li>· IMDG</li><li>· Limited quantities (LQ)</li><li>· Excepted quantities (EQ)</li></ul>	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation"	: UN1133, ADHESIVES (vapour pressure at 50 $^{\circ}\text{C}$ not mo than 110 kPa), 3, II

## SECTION 15: Regulatory information

 $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS05, GHS07
- · Signal word Danger
- $\cdot \ Hazard\text{-}determining \ components \ of \ labelling:$

methyl methacrylate methacrylic acid

2-hydroxyethyl methacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 8)

Printing date 14.08.2014 *Version number 43* Revision: 14.08.2014

Trade name: Chemsure 6002 Part B

(Contd. of page 7)

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· National regulations

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- *R*11 Highly flammable.
- R21/22 Harmful in contact with skin and if swallowed.
- R35 Causes severe burns.
- R36/38 Irritating to eyes and skin.
- R37/38 Irritating to respiratory system and skin.
- R43 May cause sensitisation by skin contact.
- · Department issuing data specification sheet: Environment protection department.
- · Contact: Sales Office
- $\cdot$  Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

\* \* Data compared to the previous version altered.